

Technical Data - Electrical Ratings

Voltage Supply	[illegible]
Signal Type	Flashing(20 fpm)
Light Colors	Red(ICAO Standard)
Power Consumption	1W
Connection	Cable
Photocell	Yes
Alarm Output	Yes
Dimensions	Check Technical Drawing
Weight Approx	3000g
Protection	IP65
Body Material	Cast Aluminium
Lens Material	Polycarbonate
Luminous Source	Power LED
Luminous Intensity	10 cd (Type A) / 32 cd (Type B)
Battery	LiFePO4
Operation Life	Strobe: 70h
Mounting	Wall Mount / Base Mount
Temperature Range	-20˚C to +50˚C

Technical Drawings

Connections



1. 12-24V/220V
2. GND/220V
3. Dry contact alarm output
4. Dry contact alarm output

Code Key

İL - XACF - L□R - SL□

AIRCRAFT WARNING LIGHT

ICAO INTENSITY CLASS

L : Low Intensity

ICAO SUBTYPE

A : ICAO Type A (10 cd)
B : ICAO Type B (32 cd)

LIGHT BODY

R : R Type Housing

SUPPLY VOLTAGE

24 : 24 VDC
48 : 48 VDC
11 : 110 VAC
22 : 220 VAC

SOLAR